

Kilsaran

KPRO REPAIR



INTRODUCING KPRO REPAIR RANGE



At Kilsaran, we have an ever-expanding range of repair products. From products formulated to repair or reinstate complete works to products designed to resurface localised areas, Kilsaran has a repair mortar to accommodate a multitude of repair or renovating needs.

All Kilsaran KPRO Repair mortars are formulated as single component products, and are produced in ISO 9001, 14001 and 50001 controlled environments. A number of KPRO Repair products are manufactured, and CE marked in accordance with EN 1504 and Construction Products Regulation No. 305/2011. Kilsaran holds EN 1504 third party factory production control certification.



Get in touch: Kilsaran, Brownstown, Kilcullen, Co Kildare, R56 VE86. Tel: 045 480620.

KPROenquiries@kilsaran.ie www.kilsaran.ie

Kilsaran

KPRO REPAIR

REPAIR RANGE



CSM-100 Resurfacing Concrete

KPRO CSM-100 is a rapid setting resurfacing mortar specifically formulated for a wide range of concrete resurfacing applications between 2mm and 15mm in depth.



CRM-203 Rapid Pavement Repair

KPRO CRM-203 is a rapid pavement repair mortar specifically formulated for a wide range of pavement repair applications between 30mm and 150mm in depth. Greater depths are possible using a layer on layer method. CRM-203 can be used as per clause 1032 and 1106 of the NRA Specification for Roadworks.



CSM-101 Surface Fairing Coat

CSM 101 is a Concrete Surfacing Mortar suitable for use internally and externally as a fairing coat on vertical or overhead soffit concrete elements. CSM 101 is one component cement based, fine grained, polymer modified Class R2 mortar, meeting the requirements of EN1504-3. CSM 101 should be used in applications for levelling the surface up to 3mm in thickness, where the concrete will not be trafficked and also receive a subsequent coating.



CRM-201 General Purpose Reinstatement Mortar

KPRO CRM 201 is a General Purpose Concrete Reinstatement Mortar suitable for both internal and external use on vertical, horizontal and overhead concrete surfaces. CRM 201 is a one component cement based polymer modified Class R3 mortar, meeting the requirements of EN1504-3. CRM 201 should be used in applications where reinstatement requires a thickness from 10mm to 70mm on vertical surfaces and up to 60mm overhead. It should be applied in accordance with EN1504-10 recommendations.



CSM-120 Rapid Floor Patch Repair Mortar

KPRO CSM-120 is a rapid setting floor patch repair mortar specifically formulated for internal and external use. CSM-120 is a self-compacting repair mortar that can be used in a wide range of applications, between 10mm and 100mm in depth. For applications greater than 50mm CSM-120 can be bulked out with a 30% addition of Kilsaran 3-5mm grit. KPRO CSM-120 meets the requirement of EN 13813 for screeding mortars.



Get in touch: Kilsaran, Brownstown, Kilcullen, Co Kildare, R56 VE86. Tel: 045 480620.

KPROenquiries@kilsaran.ie www.kilsaran.ie