



## Introducing our New LevelEase Range Your Complete Flooring Solution



### LevelEase 250

A rapid hardening and fibre reinforced cementitious levelling compound for use in domestic and commercial applications, over a multitude of substrate. Laying depth 2mm-50mm. CT-C30-F7.



### LevelEase 225

A standard-setting and fibre-reinforced cementitious levelling compound for use in domestic and commercial applications. Laying depth 2mm-25mm. CT-C25-F6.



### LevelEase Duo 225

A standard-setting two component cementitious levelling compound for use in domestic and commercial applications. Laying depth 2mm-25mm. CT-C25-F6.



### LevelEase 110

A rapid hardening self levelling compound designed for smoothing uneven floors before installing final floor coverings. Ideal for both domestic and commercial projects, it creates a smooth, level surface from 0-10mm on concrete and screeded substrates.



### LevelEase Sealing Primer

A high-performance, deep-penetrating primer designed to strengthen absorbent substrates and improve adhesion for subsequent layers. It ensures reduced absorbency and enhanced workability for a wide range of surface preparation tasks.



### LevelEase Gritty Primer

A quartz infused, high-performance and fast-setting bonding primer which delivers a textured, gritty finish that significantly enhances the adhesion of subsequent layers, to smooth non-absorbent substrates.



### LevelEase DPM

A one-component, water-based residual moisture vapor suppressant, designed to suppress residual construction moisture in cementitious substrates, where the moisture content is up to 95% RH.

#### Get in touch:

**ROI:** T: 01 801 3484 [www.kilsaran.ie](http://www.kilsaran.ie) | **UK:** T: 0161 872 8899 [www.kilsaraninternational.co.uk](http://www.kilsaraninternational.co.uk)

**Place an Order:** [orders@kilsaran.ie](mailto:orders@kilsaran.ie) **Customer Service:** [csteam@kilsaran.ie](mailto:csteam@kilsaran.ie)

**Tech Support:** [techsupport@kilsaran.ie](mailto:techsupport@kilsaran.ie)





Kilsaran

# KPRO FLOOR



|                                 |                          | LevelEase 110                                           | LevelEase 225                                           | LevelEase Duo 225                                       | LevelEase 250                                           |
|---------------------------------|--------------------------|---------------------------------------------------------|---------------------------------------------------------|---------------------------------------------------------|---------------------------------------------------------|
| Laying Dept                     |                          | 0mm – 10mm                                              | 2mm – 25mm                                              | 2mm – 25mm                                              | 2mm – 50mm                                              |
| Suitability of substrates       | Concrete                 | ...                                                     | ..                                                      | ..                                                      | ...                                                     |
|                                 | Plywood*                 | o                                                       | o                                                       | o                                                       | ...                                                     |
|                                 | S&C Screed               | ...                                                     | ..                                                      | ..                                                      | ...                                                     |
|                                 | Calcium Sulphate Screed  | ...                                                     | ..                                                      | ..                                                      | ...                                                     |
|                                 | Ceramic Tiles            | o                                                       | ..                                                      | ..                                                      | ...                                                     |
| Substrate preparation           | LevelEase Sealing Primer | Required                                                | Required                                                | Required                                                | Required                                                |
|                                 | LevelEase Gritty Primer  | Required on tiled substrates                            | Required on tiled substrates                            | Required on tiled substrates                            | Required on tiled substrates                            |
|                                 | LevelEase DPM            | If substrate moisture is $\geq 75\%$ RH, $\leq 95\%$ RH | If substrate moisture is $\geq 75\%$ RH, $\leq 95\%$ RH | If substrate moisture is $\geq 75\%$ RH, $\leq 95\%$ RH | If substrate moisture is $\geq 75\%$ RH, $\leq 95\%$ RH |
| Open to foot traffic            |                          | 2-4 hours                                               | 2-4 hours                                               | 2-4 hours                                               | 2-4 hours                                               |
| Installation of floor coverings | Tiles                    |                                                         | 12 hours                                                | 12 hours                                                | 6 hours                                                 |
|                                 | Resilient Coverings      | 24 hours                                                | 24 hours                                                | 24 hours                                                | 24 hours                                                |

\* Suitability of Substrates: ... Ideal .. Suitable o Not Suitable

## Get in touch:

ROI: T: 01 801 3484 [www.kilsaran.ie](http://www.kilsaran.ie) | UK: T: 0161 872 8899 [www.kilsaraninternational.co.uk](http://www.kilsaraninternational.co.uk)

Place an Order: [orders@kilsaran.ie](mailto:orders@kilsaran.ie) Customer Service: [csteam@kilsaran.ie](mailto:csteam@kilsaran.ie)

Tech Support: [techsupport@kilsaran.ie](mailto:techsupport@kilsaran.ie)

